

# Showcases



# Showcases

**QUALITY** Standing in Time

**SUSTAINABILITY** Respecting Nature

Guided by experience, arriving for performance, the showcase range is composed of three models of elegant design, high quality and functionality. The tempered glasses as well as the stainless steel extra shining finiture, are some of the features that ensure a vivid and attractive display.

## V-MODELS Technical Characteristics

Constructed completely in stainless steel AISI 304 18/10.

All points of contact are double bended, ensuring maximum safety

Ventilated air circulation for uniform temperature

New generation electronic touch screen thermostat with energy saving features and night mode.

Led lighting and tempered glass

Stainless steel adjustable feet for maximum hygiene and stability, or floor skirting upon request.



### Refrigerated Models

Low energy consumption  
L'Unite Tecumseh compressor, suitable for tropical climates

Copper tube condenser with painted aluminum fins to ensure maximum life duration

Adaptive defrost management and automatic water evaporation.

High quality fans

Refrigerant liquids by Linde

Two stages leakage test by high pressure Nitrogen

AISI 304



## Showcases Line VS With Straight Glass Display and Shelf



## Showcases Line VL With Straight Glass Display and two Shelves



## Showcases Line VP With Straight Parallel Glass Display



| Model                            | Temperature | Power        | Dimensions (cm.) |
|----------------------------------|-------------|--------------|------------------|
| Refrigerated Ventilated Showcase |             |              |                  |
| VS-R2                            | +2/+8° C    | 0.66 KW/230V | 85x75x125        |
| VS-R3                            | +2/+8° C    | 0.88 KW/230V | 117.5x75x125     |
| VS-R4                            | +2/+8° C    | 0.98 KW/230V | 150x75x125       |
| VS-R5                            | +2/+8° C    | 1.02 KW/230V | 182.5x75x125     |
| Heated Ventilated Showcase       |             |              |                  |
| VS-H2                            | +65/+90° C  | 1.31 KW/230V | 85x75x125        |
| VS-H3                            | +65/+90° C  | 1.32 KW/230V | 117.5x75x125     |
| VS-H4                            | +65/+90° C  | 2.02 KW/230V | 150x75x125       |
| VS-H5                            | +65/+90° C  | 2.03 KW/230V | 182.5x75x125     |
| Neutral Showcase                 |             |              |                  |
| VS-N2                            | -           | 0.01 KW/230V | 85x75x125        |
| VS-N3                            | -           | 0.02 KW/230V | 117.5x75x125     |
| VS-N4                            | -           | 0.02 KW/230V | 150x75x125       |
| VS-N5                            | -           | 0.03 KW/230V | 182.5x75x125     |

| Model                            | Temperature | Power        | Dimensions (cm.) |
|----------------------------------|-------------|--------------|------------------|
| Refrigerated Ventilated Showcase |             |              |                  |
| VS-R2                            | +2/+8° C    | 0.66 KW/230V | 85x75x125        |
| VS-R3                            | +2/+8° C    | 0.88 KW/230V | 117.5x75x125     |
| VS-R4                            | +2/+8° C    | 0.98 KW/230V | 150x75x125       |
| VS-R5                            | +2/+8° C    | 1.02 KW/230V | 182.5x75x125     |
| Heated Ventilated Showcase       |             |              |                  |
| VS-H2                            | +65/+90° C  | 1.31 KW/230V | 85x75x125        |
| VS-H3                            | +65/+90° C  | 1.32 KW/230V | 117.5x75x125     |
| VS-H4                            | +65/+90° C  | 2.02 KW/230V | 150x75x125       |
| VS-H5                            | +65/+90° C  | 2.03 KW/230V | 182.5x75x125     |
| Neutral Showcase                 |             |              |                  |
| VS-N2                            | -           | 0.01 KW/230V | 85x75x125        |
| VS-N3                            | -           | 0.02 KW/230V | 117.5x75x125     |
| VS-N4                            | -           | 0.02 KW/230V | 150x75x125       |
| VS-N5                            | -           | 0.03 KW/230V | 182.5x75x125     |

| Model                            | Temperature | Power        | Dimensions (cm.) |
|----------------------------------|-------------|--------------|------------------|
| Refrigerated Ventilated Showcase |             |              |                  |
| VS-R2                            | +2/+8° C    | 0.66 KW/230V | 85x75x125        |
| VS-R3                            | +2/+8° C    | 0.88 KW/230V | 117.5x75x125     |
| VS-R4                            | +2/+8° C    | 0.98 KW/230V | 150x75x125       |
| VS-R5                            | +2/+8° C    | 1.02 KW/230V | 182.5x75x125     |
| Heated Ventilated Showcase       |             |              |                  |
| VS-H2                            | +65/+90° C  | 1.31 KW/230V | 85x75x125        |
| VS-H3                            | +65/+90° C  | 1.32 KW/230V | 117.5x75x125     |
| VS-H4                            | +65/+90° C  | 2.02 KW/230V | 150x75x125       |
| VS-H5                            | +65/+90° C  | 2.03 KW/230V | 182.5x75x125     |
| Neutral Showcase                 |             |              |                  |
| VS-N2                            | -           | 0.01 KW/230V | 85x75x125        |
| VS-N3                            | -           | 0.02 KW/230V | 117.5x75x125     |
| VS-N4                            | -           | 0.02 KW/230V | 150x75x125       |
| VS-N5                            | -           | 0.03 KW/230V | 182.5x75x125     |

**HYGIENE & SAFETY** The Cornerstone of Every Kitchen

**DESIGN** Industrial Elegance



## **Bountourakis S.A.**

C street, 1A, 71601  
Heraklion Industrial Area,  
Crete, Greece

T: 2810 380991

F: 2810 380992

[info@bountourakis.com](mailto:info@bountourakis.com)

[www.bountourakis.com](http://www.bountourakis.com)

